



PED
2014/68/ CE
CAT. II

TSR



ZW



FW2



Triplex pumps with ceramic
pistons and brass pump head

FOR MORE
INFORMATION



BOX DIMENSION (cm)	100 x 73 x 105
QUANTITY FOR PALLET	1
PALLET DIMENSION (cm)	100 x 73 x 105
N. MACHINES CONTAINER 20'	34
N. MACHINES CONTAINER 40' (40' HQ)	68

KM STEEL



Handle for practical use



Single central bar for vertical
lifting with crane or winches



Professional control panel.
Electronic temperature regulation
system with low oscillation of the
set value.



Professional
pressure-release
unloader valve



Detergent regulator with
connector on the front



Motor-pump coupling with
a flexible joint (7,5 / 10 HP
models only)



Front and rear protective
bumper also useful for
improving maneuverability
and safety in manual lifting
operations



GENERAL FEATURES

- 25 lt fuel tank with level float
- High-pressure detergent suction with proportional detergent regulation
- 4 big solid wheels (Ø 260 mm) + brake
- Water tank with cartridge filter and floater
- Anti-scale device with pump and tank (2,5 l - ON REQUEST)
- Professional 4-pole motor (1400 giri/min) with flexible joint (7,5 / 10 HP models only)
- Professional pressure unloader valve
- 15 seconds Delayed Total Stop
- General stop when the machine is not used for a long time (30 minutes)
- EASY START on 1-230 model
- Boiler with stainless steel casing (7,5 / 10 HP models only)
- Electronic temperature regulation system with low oscillation of the set value
- PED 2014/68/CE cat. II certification
- Flow-switch controlled burner
- Flame control
- Safety valve
- Boiler thermal protection
- Pressure gauge with S.S. frame